

**PRODUCT NAME:** Water Softener

Pro Water Parts systems use advanced ion exchange resin technology in order to meet the most demanding water conditions. These systems are designed for maximum performance with a minimal amount of maintenance and comply with all industry standards and specifications.

- STANDARD FEATURES:**
- Fleck metered control valve
  - Easy to program SXT electronics
  - Pre-treat lockout contacts
  - 48 hour power backup
  - Day of the week controls
  - Regeneration can be triggered immediately
  - Structural heavy duty fiberglass tank
  - Heavy duty riser pipe with upper and lower screens
  - 10% cross-link ion exchange resin
  - Brine tank with float assembly and salt grid



Part Number	Valve	Voltage	DLFC	Connection (in)	Approx GPD Capacity	Tank Size (in)	Cubic Feet	Tank Quality	Brine Tank Size (in)	Backwash Rate (gpm)	Recommended Service Flow Rate (gpm)	Estimated Peak Flow (gpm)
PWS3411010G	5600SXT	110V	3	3/4 MNPT	45,000	10 x 54	1.5	1	18 x 33	3	1.6 - 10.0	10.0
PWS3422010G	5600SXT	220V	3	3/4 MNPT	45,000	10 x 54	1.5	1	18 x 33	3	1.6 - 10.0	10.0
PWS111015G	7000SXT	110V	4	1 MNPT	60,000	12 x 52	2	1	18 x 33	4	2.3 - 15.0	15.0
PWS122015G	7000SXT	220V	4	1 MNPT	60,000	12 x 52	2	1	18 x 33	4	2.3 - 15.0	15.0
PWS111020G	7000SXT	110V	7	1 MNPT	120,000	16 x 65	4	1	24 x 40	7	4.2 - 20.0	20.0
PWS122020G	7000SXT	220V	7	1 MNPT	120,000	16 x 65	4	1	24 x 40	7	4.2 - 20.0	20.0
PWS1511045G	2850S SXT	110V	12	1.5 FNPT	180,000	21 x 62	6	1	24 x 54	12	13.0 - 45.0	45.0
PWS1522045G	2850S SXT	220V	12	1.5 FNPT	180,000	21 x 62	6	1	24 x 54	12	13.0 - 45.0	45.0